

# PURE GUARD

## PRODUCT DATA BULLETIN

### PURE GUARD GLOBAL AUTOMATIC TRANSMISSION FLUID

#### DESCRIPTION AND APPLICATIONS

**PURE GUARD Global ATF** is a premium fluid designed for automatic transmissions of all North American, European, and Asia-Pacific-made vehicles. **PURE GUARD Global ATF** provides exceptional oxidation, wear, frictional stability, and anti-shudder properties required in today's high performance transmissions. It also designed to deliver premium performance in older transmissions.

#### Product Specifications:

Specific Gravity @60°F (H <sub>2</sub> O=1)	0.86 - 0.88
Viscosity, @ 100°C, cSt, typ.	7.6
Brookfield Viscosity, cP, max	13,000
Flash Point, °F (°C) Min.	330 (165)
Pour Point, °C (F)	< -43 (-45.40)
Color and Appearance	Red liquid

#### Packaging Specifications:

Bottle 32 fluid ounces (946 ml), HDPE plastic bottle

#### Product Claims:

**PURE GUARD Global ATF** Meets or exceeds requirements of Ford's Mercon V. Will perform satisfactory in Mercon SP, Dexron-VI and Toyota WS applications. Suitable for Chrysler vehicles where ATF+4 and ATF+3 are required.

It can also be used where fluids meeting Ford ESP-M2C138CJ or Ford M2C166-H specifications are required. Exceeds Alison C4 specifications. Recommended for Mercedes transmissions. Not recommended for use where Ford Type F fluid is required.

Detailed list of recommended specifications is below:

<b>Manufacturer</b>	<b>Specification</b>
Acura	ATF-Z1 (Except in CVTs)
Allison	C-4
Audi	G-055-025-A2
BMW	LA2634,LT71141; Texaco ETL-7045-E, ETL-8027B, Shell M1375.4
Chrysler	ATF+4®, ATF+3®, ATF+2®, ATF+®
Ford	MERCON SP®, MERCON LV®, MERCON V®,MERCON®,XT-9QMM5
General Motors	DEXRON VI®, DEXRON V, DEXRON III®, 9986195, Type A, Suffix A (TASA)
Honda	ATF-Z1 (except in CVTs)
Hyundai	SP-II, SP-III
Idemitsu	K17

# PURE GUARD

## PRODUCT DATA BULLETIN

---

Infinity	Matic-D, Matic-J, Matic-K
Isuzu	Genuine
Jaguar	Shell M1375.4
Kia	All Specifications
Land Rover	Texaco N402, Shell M1375.4
Lexus	Type T, T-III, T-IV
MAN	339F
Mazda	ATF M-V
Mercedes Benz	Sheet 236.x
Mitsubishi	Diamond SP-II, SP-III
Nissan	Matic-D, Matic-J, Matic-K
Saab	Transmax J
Subaru	All specifications
Toyota	Type T, T-III, T-IV
Voith	55.6335.32 (G607)
Volvo	All specifications
Volkswagen	TL52162, G052 990
ZF	TE-ML 03D, 04D, 14A, 14B, 16L, 17C
Various (Aisin-Warner Transmissions)	JWS-3309

### **Hazards:**

Contains Petroleum Distillates. Use with adequate ventilation. Keep away from heat, flame and all other sources of ignition. Avoid prolonged contact with skin. In case of contact, wash thoroughly with soap and water. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.